



可變容量輪葉泵浦 + 齒輪泵浦

VARI-DISP. VANE PUMPS & GEAR PUMPS

TCVG-F23,F26,F30,F40+PA



特點：

- 共用同一心軸及馬達，節省空間，本組合泵因採用一小流量之齒輪泵，而形成依高低泵組合。
- 噪音小、效率高，運轉滑順。

FEATURES:

- Employed same shaft & motor, save occupied space, Since, this combination pump is adopted a small flow rate gear pump and formed a hi-low pressure pump set.
- Low noise level, hi-efficiency, and running smoothly.

訂購索引

ORDERING INDEX

TCVG - F ※ - H ※ - PA - 02

設計號碼 Design no.

吐出能力 Delivery capacity (齒輪泵 Gear pump)

PA1, PA2, ..., PA6, HR1, HR2 (2~12c.c/rev.)

壓力範圍 Pressure range

1: 15~35bar , 2: 20~70bar

3: 50~105bar , 4: 70~140bar

吐出能力 Delivery capacity (可變容量輪葉泵 Vari-disp. vane pump)

1: 23L/min , 2: 26L/min , 3: 30L/min , 4: 40L/min

安裝方式 Mounting style

F: Flange mounting (法蘭式)

系列號碼 Serial no.

規格

SPECIFICATIONS

型式 Model	齒輪泵 Gear pump		可變量泵 Vari-disp. vane pump		額定速度 Rated speed	
	最大壓力 Max. pres.	吐出能力 Deliv. Cap.	壓力範圍 Pressure range	吐出能力 Deliv. Cap.	最高 Max.	最低 Min.
TCVG-F23	3000psi	2~12c.c/rev.	15~35bar	23L/min	1800rpm	800rpm
TCVG-F26			20~70bar	26L/min		
TCVG-F30			50~105bar	30L/min		
TCVG-F40			70~140bar	40L/min		

壓力調整螺絲
Pressure adjustment

