



雙連式可變容量輪葉泵浦

VARI-DISPLACEMENT TWIN VANE PUMPS

TCVVP-F2323,F2626,F3030,F4040



特點：

- 本系列泵浦，操作時噪音小，運轉滑順耐磨耗，適用於工作母機及專用機使用。
- 溫昇小，馬力損失小，內臟式自動壓力補償設計。

FEATURES:

- This series pump which being with low noise level,running smoothly and wear resistant,Especially,those are very suitable for machinetool&specialpurpose m/c use.
- Little temp upward&little power lose and designed of auto emersed pressure compensating.

訂購索引

ORDERING INDEX

TCVVP - F※※ - H※ - H※ - 02

設計號碼 Design no.

壓力範圍 Pressure range (蓋端Cover end)

1:15~35bar , 2:20~70bar

3:50~105bar , 4:70~140bar

壓力範圍 Pressure range (軸端Shaft end)

1:15~35bar , 2:20~70bar

3:50~105bar , 4:70~140bar

吐出能力 Delivery capacity(蓋端Cover end)

1:23L/min , 2:26L/min , 3:30L/min , 4:40L/min

吐出能力 Delivery capacity(軸端Cover end)

1:23L/min , 2:26L/min , 3:30L/min , 4:40L/min

安裝方式 Mounting style

F:Flange mounting (法蘭式)

系列號碼 Serial no.

規格

SPECIFICATIONS

型式 Model	吐出能力 Delivery capacity (1800 rpm)		壓力調整範圍 Pressure adj. range	額定速度 Rated speed	
	前泵 Front pump	後泵 Rear pump		最高 Max.	最低 Min.
TCVVP-F2323	23 l/min	23 l/min	15~35bar 20~70bar 50~105bar 70~140bar	1800rpm	800rpm
TCVVP-F2626	26 l/min	26 l/min			
TCVVP-F3030	30 l/min	30 l/min			
TCVVP-F4040	40 l/min	40 l/min			

